

EVOQUE

SERIES

CLUB / DISCOTHEQUE / LOUNGE SYSTEMS



LLOYD[®]
LEE
COMPANY
PRO SOUND
SINCE 1979

EVOQUE custom designed installs are more than sound systems; they are perpetual marketing tools for your venue. A system that never fails to impress your customers is worth far more than the cost of the system. EVOQUE systems are crafted not only to deliver top-notch sound, but also reliability for rock-solid performances year after year.

Lloyd Lee Co. enjoys an unmatched reputation in the night club scene having successfully integrated custom designs and standard product lines that have been acknowledged by many. Be it an extraordinary music event or extravagant venue layout, it takes various elements of attraction to achieve the desired effect. Sound is the core and one of the most important aspects of an event. We believe

that providing audiences with an exceptional sound experience, evokes the desire in people to continually visit venues for that same awesome feeling. We achieve this by paying attention to every detail on the professional sound systems acoustic performance, which combines accurate system design along with perfect room acoustics.

RELIABILITY FOR ROCK

EVOQUE LINE **8**

1X8 INCH LF + 1.4 HF INCH 2 WAY LINE ARRAY SPEAKER

■ FEATURES

- 300W AES, 1200W peak, constant curvature line array system.
- Very high output coupled with clean and precise sound reproduction.
- Fast, integral, high strength rigging system.
- 1x8 inch Italian 300W high performance mid-bass speaker.
- 1x1.4 inch exit B&C compression driver for power and performance.



EVOQUE LINE **8F**

1X8 INCH LF + 1.4 HF INCH 2 WAY LINE ARRAY SPEAKER

■ FEATURES

- 300W AES, 1200W peak, constant curvature line array system.
- Very high output coupled with clean and precise sound reproduction.
- Fast, integral, high strength rigging system.
- 1x8 inch Italian 300W high performance mid-bass speaker.
- 1x1.4 inch exit B&C compression driver for power and performance.



EVOQUE SATELLITE **8**

1X 8 INCH LF + 1 INCH HF 2 WAY FULL-RANGE LOUDSPEAKER

■ FEATURES

- 300W continuous, 1200W peak power handling.
- Passive 2 way high-output full-range.
- 8 inch Italian LF transducer.
- Ultra-compact multipurpose design.
- Unique elliptical horn.



EVOQUE SATELLITE 10

1X10 INCH LF + 1 INCH HF 2 WAY FULL-RANGE LOUDSPEAKER

■ FEATURES

- 350W continuous, 1200W peak power handling.
- Passive 2 way high-output full-range.
- 1 inch exit pure titanium B&C HF compression driver.
- Specialised B&C 10 inch LF transducer with weather protected cone.
- Ultra-compact multipurpose design.



SOLID PERFORMANCE

EVOQUE MODULE 12

1X12 INCH LF + 1.4 INCH HF 2 WAY FULL-RANGE LOUDSPEAKER

■ FEATURES

- 700W AES, 2800W peak power handling.
- Compact multipurpose design.
- Passive 2 way very high-output full range.
- 1.4 inch exit B&C compression driver for high power and precise vocal reproduction.
- 12 inch long excursion high power B&C woofer with weather protected cone.



EVOQUE SUBWOOFER 15

1X15 INCH COMPACT SUBWOOFER

■ FEATURES

- 600W continuous, 2400W peak power handling, 8 ohms.
- Very compact design.
- pole mount to elevate two-way loudspeaker.
- Direct radiating Vented LF enclosure, solid bass down to 35hz.
- 15 inch low distortion B&C LF transducer with weather protected cone.



EVOQUE SUBWOOFER 18

1X18 INCH SUBWOOFER SYSTEM

■ FEATURES

- 1200W AES, 4000W peak power handling, 8 ohms.
- Extended low frequency reproduction and excellent transient response.
- 18 inch cutting edge technology with B&C woofer for extremely high-power.
- Very compact design with pole mount to elevate two-way loudspeaker.
- Enclosure is stackable in both horizontal and vertical orientations.



EVOQUE

TECHNICAL SPECIFICATIONS	LINE 8	LINE 8F	MODULE 12	SATELLITE 8
TYPE	Two-way, compact line array module	Two-way, compact line array module	Two-way compact (full-range)	Two-way compact (full-range)
FREQUENCY RANGE	60Hz-18kHz	60Hz-18kHz	55Hz-19kHz	75Hz-18kHz
DRIVERS LF	1 x 8 inch reflex-loaded direct radiator	1 x 8 inch reflex-loaded direct radiator	1 x 12 inch reflex-loaded direct radiator	1 x 8 inch reflex-loaded direct radiator
DRIVERS HF	1 x 1.4 inch exit HF compression driver, horn loaded	1 x 1.4 inch exit HF compression driver, horn loaded	1 x 1.4 inch exit HF compression driver, horn loaded	1 x 1 inch exit HF compression driver, horn loaded
RATED POWER	Passive: 300W AES, 1200W Peak LMF: 300W AES, 1200W Peak HF: 80W AES, 320W Peak	Passive: 300W AES, 1200W peak LMF: 300W AES, 1200W peak HF: 80W AES, 320W peak	Passive: 700W AES, 2000W peak LMF: 700W AES, 2800W peak HF: 100W AES, 400W peak	Passive: 300W AES, 800W peak LMF: 300W AES, 1200W peak HF: 40W AES, 160W peak
SENSITIVITY	97 dB	97 dB	100dB	97dB
MAXIMUM SPL (CALCULATED @ 1M)	118dB continuous, 124dB peak	118dB continuous, 124dB peak	126dB continuous, 132dB peak	118dB continuous, 124dB peak
NOMINAL IMPEDANCE	8 ohms	8 ohms	8 ohms	8 ohms
DISPERSION (-6db)	100° horizontal x 15° vertical	60° horizontal x 10° vertical	70° horizontal x 50° vertical (Rotatable)	90° horizontal x 60° vertical
CROSSOVER	1.2kHz (Passive)	1.2kHz (Passive)	1.4kHz (Passive)	1.7kHz (Passive)
ENCLOSURE	Vertical Trapezoid , BWP ply construction	Vertical Trapezoid , BWP ply construction	Trapezoid , BWP ply construction	Trapezoid , BWP ply construction
FINISH	Lloyd Lee Co. weather resistant textured paint cover	Lloyd Lee Co. weather resistant textured paint cover	Lloyd Lee Co. weather resistant textured paint cover	Lloyd Lee Co. weather resistant textured paint cover
PROTECTIVE GRILLE	Perforated Steel Powder Coated, 16G.	Perforated Steel Powder Coated, 16G.	Perforated Steel Powder Coated, 16G.	Perforated Steel Powder Coated, 16G.
CONNECTORS	2 x Neutrik NL4	2 x Neutrik NL4	2 x Neutrik NL4	2 x Neutrik NL4
DIMENSIONS	531 mm x 246 mm x 342 mm (WxHxD)	531 mm x 246 mm x 342 mm (WxHxD)	335 mm x 612 mm x 396 mm (WxHxD)	259 mm x 412 mm x 245 mm (WxHxD)
WEIGHT	19kg (Approx)	19kg (Approx)	29kg (Approx)	12kg (Approx)

TECHNICAL SPECIFICATIONS	SATELLITE 10	SUBWOOFER 15	SUBWOOFER 18	MONITOR 12P
TYPE	Two-way compact/moniyor (full-range)	Subwoofer	Subwoofer	
FREQUENCY RANGE	60Hz-18kHz	41Hz-120kHz	25Hz-250kHz	
DRIVERS LF	1 x 10 inch reflex-loaded direct radiator	1 x 15 inch reflex-loaded direct radiator	1 x 18 inch reflex-loaded direct radiator	
DRIVERS HF	1 x 1 inch exit HF compression driver horn loaded	NA	NA	
RATED POWER	Passive: 350W AES, 2000W Peak LMF: 350W AES, 2800W Peak HF: 80W AES, 320W Peak	600W AES, 2400W peak	1200W AES, 4000W peak	
SENSITIVITY	99 dB	98 dB	98 dB	
MAXIMUM SPL (CALCULATED @ 1M)	120dB continuous, 126dB peak	120dB continuous, 126dB peak	127dB continuous, 133dB peak	
NOMINAL IMPEDANCE	8 ohms	8 ohms	8 ohms	
DISPERSION (-6db)	90° horizontal x 60° vertical (Rotatable)	NA	NA	
CROSSOVER	1.7kHz (Passive)	NA	NA	
ENCLOSURE	Trapezoid , BWP ply construction	Rectangular, BWP ply construction	Rectangular, BWP ply construction	
FINISH	Lloyd Lee Co. weather resistant textured paint cover	Lloyd Lee Co. weather resistant textured paint cover	Lloyd Lee Co. weather resistant textured paint cover	
PROTECTIVE GRILLE	Perforated Steel Powder Coated, 16G.	Perforated Steel Powder Coated, 16G.	Perforated Steel Powder Coated, 16G.	
CONNECTORS	2 x Neutrik NL4	2 x Neutrik NL4	2 x Neutrik NL4	
DIMENSIONS	351 mm x 555 mm x 291 mm (WxHxD)	460 mm x 554 mm x 490 mm (WxHxD)	686 mm x 547 mm x 574 mm (WxHxD)	
WEIGHT	16kg (Approx)	32kg (Approx)	47g (Approx)	

LLOYD LEE CO.

Mobile: 9833374789/9820307275
Email Add: sales@lloydleecompany.com
Website: www.lloydleecompany.com

Note: Specifications are subject to change without prior notice.